

 **Flavy FX 1 / 2 / 3**



Flavy FX 3

The new range Flavy FX1, FX2 and FX3 is the best answer to small wineries requirements.

- Respect of the wine organoleptic quality as structure, color, aromas ...
- Minimal wine losses thanks to the inert gas « pushing process ».
- Decrease of the wine oxidation thanks to the absence of oxygen in the filter unit.
- Fully automatic filtration process.
- Optimized price per gallon, or per liter.
- Dead volumes designed to reduce wine losses and water consumption.



Flavy FX 1



Flavy FX 2

Technical characteristics

Model	Number of modules	Filtration surface (m ²)	Length (mm)	Height (mm)	Width (mm)	Empty weight (kg)	Power (kW)
FX 1	1	12	1252	842	1868	250	3.75
FX 2	2	24	1568	861	1834	325	4.75
FX 3	3	36	1836	861	1834	400	8.6

Fitting dimensions

- Wine in / out : DIN 40
- Retentate and back flush output : DIN 40
- Water fitting : F 1 " Gaz
- Air / Nitrogen fittings : 10 bar, F ¼ " Gaz
- Equipression fittings : F ¾ " Gaz


Average flows obtained during trials

Wines	FX 1	FX 2	FX 3
Dry white wine	12 hl/h	24 hl/h	36 hl/h
Gross rose wine	7 hl/h	14 hl/h	21 hl/h
Gross red wine	6 hl/h	13 hl/h	19 hl/h
Prefiltered red wine	11 hl/h	21 hl/h	32 hl/h

Options



Dosing pump for chemicals



Turbidimeter (except for FX 1)



Water filters



Sparkling wines

Distributed by :

Bucher Vaslin
Rue Gaston Bernier – BP 70028
F - 49290 Chalonnes sur Loire
Tel. +33 (0)2 41 74 50 50
Fax +33 (0)2 41 74 50 51
E-mail : commercial@buchervaslin.com

www.buchervaslin.com
Your success is our priority

Non contractual documentation, the manufacturer has the right to make modifications without notice.