



F.V.S. TOP Manure spreaders



With rigid suspension and localised spreading on rows in vineyards orchards, etc. Complete with no. 2 adjustable casings for localised distribution on the row. The structure is made of cut tube profiles with pickled sheet steel. The deck and sides are made of treated larch planks. Special guides for chain running, extensible drawbar complete with wheel-arch, axle without brake. Without the road lighting/indication system.

F.V.S. TOP Manure spreaders

Rotary manure spreader with the super "S" special rotator with 2 powered driving caps, **COMPLETE WITH EDGE WITH CHAIN FEED, HYDRAULIC ENGINE FOR BINDING CHAIN**, with a hydraulic control valve for speed regulation and a direction inverter with quick coupling operation of the tractor.

Mod. 1200	A	Y	B	C	D	F	G	H	I TYRES	M ³	Empty weight Kg	Space between rows
F.V.S. 25 TOP VIGNERON	300	85	405	140	460	145	120	155	10/75/15 12 PR	2.50	1380	180
F.V.S. 35 TOP VIGNERON	370	85	455	140	520	145	120	155	10/75/15 12 PR	2.90	1500	180
NEW F.V.S. 40 TOP VIGNERON	400	85	495	150	550	155	130	165	11/80/15 16 PR	3.30	1680	300
F.V.S. 45 TOP VIGNERON	450	85	565	150	600	155	130	165	11/80/15 16 PR	3.60	1750	300

Mod. 1300	A	Y	B	C	D	F	G	H	I TYRES	M ³	Empty weight Kg	Space between rows
F.V.S. 25 TOP	320	85	415	140	470	165	130	165	10/75/15 12 PR	3.00	1470	210
F.V.S. 35 TOP	370	85	465	140	520	165	130	165	10/75/15 12 PR	3.30	1550	210
NEW F.V.S. 40 TOP	400	85	495	150	550	185	130	185	13.0/65-18 16 PR	3.50	1680	300
F.V.S. 45 TOP	450	85	565	150	600	185	130	185	13.0/65-18 16 PR	4.00	1750	300

ACCESSORIES ON REQUEST: SEE PAGE 54, 55

STANDARD:



F.V.S. TOP Spreader

Super "S" special rotator with 2 powered driving caps and chain transmission as standard supply



engine for hydraulic binding chain

STANDARD
EQUIPMENT



edge with chain feed

Mod. F.V.S. TOP

